

CMP-CT SERIES

DOUBLE MASTS AERIAL WORK PLATFORM

Mantall®



Standard Features

- Polyurethane Non-mark tires
- Forklift Pockets
- Foldable Inclined Ladder
- Two controls: Platform Control and Ground Control
- Lower Beeper warning
- Emergency Lower Down
- Maintenance-free battery

Options Features

- Narrow/Rough Ground Chassis
- DC Power
- Tool Box
- Platform Positioning Laser light
- Fluorescent Tubes Box
- Working Flashing Beacon
- Top Limit Protection Auto-stop device
- Auxiliary drive wheel
- Equipment Protection cover

CMP-CT SERIES

MODEL	CMP12CT	CMP14CT	CMP16CT
Working height max H1	12 m	14 m	16 m
Platform height max H2	10 m	12 m	14 m
Lift capacity	250 kg	200 kg	150 kg
Platform Size B x C x A	1.44 x 0.6 x 1.1 m		
Overall length E	1.74 m	1.81 m	1.81 m
Width F	0.81 m		
Stowed height D	1.86 m	2.08 m	2.36 m
Outrigger expansion I x K	2.45 x 2.34 m		
Minimum ground clearance	0.07 m		
Power unit (AC)	220V / 1.5kW		
Power unit (DC)	12VDC / 1.6kW		
Battery	12V/120Ah		
Charger	12V/15A		
Caster (front wheels)	8 in		
Caster (rear wheels)	6 in		
Weight (AC/DC)	760 / 830 kg	844 / 880 kg	909 / 940 kg

